

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5 - 1608100

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Push/pull connector (version 14), metal, with RJ45 QUICKON connector, 4-pos., with QUICKON fast connection technology, for 1-wire and 7-wire conductors 22 AWG, for a cable diameter of 5.0 mm ... 8.0 mm

Push/pull connector



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 159944
Weight per Piece (excluding packing)	67.04 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	4
Connection profile	RJ45 8(4)
Locking type	Push Pull
Shielded	Yes
Insertion/withdrawal cycles	≥ 500
Connection method	IDC fast connection
Conductor cross section	0.13 mm ² ... 0.32 mm ² (solid) 0.14 mm ² ... 0.36 mm ² (stranded)
Connection cross section AWG	26 ... 22 (solid) 26 ... 22 (stranded)
External cable diameter	5 mm ... 8 mm
Cable exit	Straight
Color	silver

Ambient conditions

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5 - 1608100

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP65/67

Material data

Inflammability class according to UL 94	V0
Housing material	Zinc die-cast
Housing surface material	Nickel-plated
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material, O-ring	NBR
Cable seal material	TPE
Material housing intermediate seal	NBR

Electrical characteristics

Number of positions	4
Nominal voltage U_N	50 V
Nominal current I_N	1.75 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)
Rated current	1.75 A
Surge voltage category	I
Pollution degree	2

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27261204
eCl@ss 7.0	27440205
eCl@ss 8.0	27440205

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC002641

UNSPSC

UNSPSC 6.01	30211923
-------------	----------

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5 - 1608100

Classifications

UNSPSC

UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized	
mm ² /AWG/kcmil	22
Nominal current I _N	1.75 A
Nominal voltage U _N	50 V

cUL Recognized	
mm ² /AWG/kcmil	22
Nominal current I _N	1.75 A
Nominal voltage U _N	50 V

cULus Recognized	
------------------	--

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5 - 1608100

Accessories

Accessories


Tool - VS-CABLE-STRIP-VARIO - 1657407



Stripping tool, for the multi-level stripping of shielded cables

Drawings

Dimensioned drawing



Push-pull RJ45 connector IP65/67